

Volk Service Car, type DFZ 10N



Towing capacity: Approx. 20 ton (even ground)
Starting aid: 12 and 24 voltage
Width: 1025 mm
Length: 3070 mm
Height: 1600 mm
Weight: 1845 kg

Each Höegh Autoliners vessel have one service car, which shall be used as a jump starting-, towing- and an internal service car. The service car is lowbuilt and can be used on all decks.

When used as a towing car, please use a long rope or towbar between the towed unit and the Volk Service Car.

Please pay attention to safety rules when driving and always drive with all lights on, in order to be seen at all times.

Check List Volk Service Car

Customer:		<i>Sample</i>		Ship:		<i>Sample</i>	
Equipment:		<i>Sample</i>		Serial-number:		<i>Sample</i>	
Date:		Mechanic:		Hourmeter:		<i>Sample</i>	
		Level 1	Level 2			Level 1	Level 2
		X	X			X	X
1. Cab/Chassis				5. Brake system			
1.1	Tires	X	X	5.1	Function	X	X
1.2	Rims		X	5.2	Brake-fluid level	X	X
1.3	Wheel bolts/nuts		X	5.3	Lining Wearing		X
1.4	Test of all functions	X	X	5.4	Parking brake	X	X
1.5	Lubrication		X				X
1.6	Hoods/covers	X	X	6. Steering			
2. Electrical system				6.1	Spindle		X
2.1	Batteries	X	X	6.2	Ball joint	X	X
2.2	Charging	X	X	6.3	Bearings		X
2.3	Lights	X	X	6.4	Steering cylinder		X
2.4	Horn	X	X	6.5	Spring		X
2.5	Preheating engine	X	X	7. Hydraulic system			
2.6	Instruments & meters	X	X	7.1	Oil level/quality	X	X
2.7	Switch Component	X	X	7.2	Filter (1000 h)		X
2.8	Cable drum/Connect	X	X	7.3	Valves/Hoses	X	X
3. Engine							
3.1	Change oil & Filter	Level	X				
3.2	Fuel filter	X	X				
3.3	Coolant	X	X				
3.4	Fan belts	X	X				
3.5	Air filter		X				
4. Transmission							
4.1	Gearshift function	X	X				
4.2	Drive motors		X				
4.3	Back up function	X	X				
				Done:		Date:	

